# **SC2-SM SERIES**

**UNDERWATER LIGHT** 



### DESCRIPTION

The SC2 underwater light provides your vessel 24 watts of intense LED lighting. The SC2's are designed with a sub-compact 2.99" composite or bronze housing for under the waterline surface mounting. Single color and color changing versions available with variable brightness and a wide array of control options.

#### **FEATURES**

- Proprietary clear gel-filled design, injected through entire unit eliminates condensation and/or water intrusion under stress
- Tough, scratch resistant, tempered glass lens with either composite or bronze housing — impervious to acetone, solvents and demanding marine environments
- Transient surge and reverse polarity protection — dramatically prolongs unit life
- Thermal throttling technology enables safe operation even out of water
- From simple on-off to full-feature lighting effects, unit is enabled for a host of control interfaces

# **SPECIFICATIONS**

- Up to 3,000 lumens
- 120 degree beam angle
- 24 watt power draw
- 2 amps operating current draw @ 12V
- 10-30 volts input
- 2.99" (75.9mm) outside diameter
- IP68 fully submersible waterproof design

#### **INCLUDES**

- · Lighting unit
- 3' (1m) submersible grade cable
- 3 mounting screws
- 3 year standard warranty

#### **2 CONTROL OPTIONS**

Power Toggle Control
 Quickly toggle power source to advance to next color or brightness level

#### 2. Add Shadow-NET™ Control

Dramatic, full-feature control through your Multifunction Display (MFD) by adding the Shadow-NET<sup>™</sup> control module (SCM-LC-PLUS)

## Shadow-NET™ Modes

- · Unlimited shades of color and fading
- Dimming Strobe rate Music sync
- Multiple zones
   And much more...

Dramatically enhanced lighting capabilities through your existing MFD



SC2-SM SERIES LIGHT COLOR MODELS		GREAT WHITE	BIMINI BLUE/ GREAT WHITE	FULL COLOR 12-color standard, or unlimited colors with Shadow-NET
BRONZE VERSION MODEL #	SC2-BB-BZSM	SC2-GW-BZSM	SC2-BW-BZSM	SC2-CC-BZSM
COMPOSITE VERSION MODEL #	SC2-BB-CSM	SC2-GW-CSM	SC2-BW-CSM	SC2-CC-CSM
BADGE IDENTIFIER	(SE	(SE	(SE	<b>5C</b>